


# GENERATING SET

# GE804 Ii06



## PERFORMANCES

RATINGS	50 Hz		60 Hz	
	kVA	kWe	kVA	kWe
<b>PRIME</b>	<b>40</b>	<b>32</b>	<b>47</b>	<b>38</b>
<b>STAND-BY</b>	<b>44</b>	<b>35</b>	<b>52</b>	<b>42</b>

Ratings in accordance with ISO 8528 - Standard reference conditions : 25°C air inlet temperature ; 1000 mbar ; 30% relative humidity - Power factor 0.8 .

### PRIME POWER

The Prime Power is the maximum power available with varying loads for an unlimited number of hours. The average power output during a 24 h period of operation must not exceed 80% of the declared prime power between the prescribed maintenance intervals and at standard environmental conditions. A 10% overload is permissible for 1 hour every 12 hours of operation.

### STAND-BY POWER

This is the maximum power available for a period of 500 hours/year with a mean load factor of 90% of the declared stand-by power. No kind of overload is permissible for this use.

## TECHNICAL DATA

Engine model	804 Ii06	Frequency	<b>50 Hz</b>	<b>60 Hz</b>		
N° of cylinders	4 in line	Fuel consumption* at : 100% load	l/h	9.9	11.9	
Total displacement	liters 3.9	75% load	l/h	7.3	9.0	
Aspiration	natural	50% load	l/h	5.2	6.2	
Cooling system	liquid (water + 50% Paraflu I I)	* medium consumption according to PRP (ISO 8528-1)				
Lube oil consumption	< 0.3% of fuel consumption	Available voltages	V	110/190 to 120/208	230/400 to 254/440 (50 Hz)	230/400 to 277/480 (60 Hz)
Generating set dimensions (L x W x H)	mm 1645 x 700 x 1060	Dry weight with standard accessories	kg	~ 815		

## STANDARD CONFIGURATION

### 1. ENGINE DRIVE

IVECO heavy duty diesel engine.

#### 1.1 Governor

Mechanical, compliance with ISO 8528, class G2.

### 2. COOLING SYSTEM

Radiator and pusher fan dimensioned for tropical climates. The radiator is mounted on the base frame to avoid vibrations coming from the engine and is equipped with adequate security protection guards.

### 3. FILTRATION SYSTEM

The engine is equipped with: dry air filter, fuel filter and oil filter. All filters have replaceable cartridges.

### 4. EXHAUST SYSTEM

Industrial application exhaust silencers are supplied assembled on the engine or loose.

### 5. ELECTRICAL SYSTEM

12 Volt system with battery charging alternator. Starter motor. High performance maintenance free lead acid battery (on request). Battery rack mounted on the generating set base frame.

### 6. ALTERNATOR

Single bearing synchronous brushless alternator, four poles, mechanical protection degree IP21 and H class insulation. Standard connections: 12 terminals - 9 leads reconnectable. Tropical climates impregnation; on request, humid and corrosive climates treatment. All alternators are equipped with electronic voltage regulator.

### 7. MOUNTING ARRANGEMENT

#### 7.1 Base Frame

The complete generating set is mounted on a modern design and high quality steel fabricated base frame, bended without weldings, painted with epoxy coating. In the catch all base frame are located the fuel tank and the batteries.

Anti vibration pads are fitted between engine-alternator and base frame ensuring complete vibration isolation of rotating assemblies.

#### 7.2 Coupling

Engine and alternator are directly coupled. The engine flywheel is coupled to the alternator rotor by means of flexible disks.

### 8. FUEL SYSTEM

Thermoplastic fuel tank with a total capacity of 80 liters is provided on the base frame. The fuel tank is equipped with a visual fuel level indicator. An oversized fuel tank of a capacity of 500 liters is available as option. Fuel tanks with special certifications are also available on request.

### 9. CONTROL PANEL

Manual and Automatic control panels are available in different configurations.

### 10. OPTIONS

Generating set can be supplied with different options to meet the specific requirements of the customer (see specific brochure).

### 11. DOCUMENTATION

A full set of operation and maintenance manuals are provided with each unit.

### 12. FACTORY TESTS

Generating set is subject to a strict load test before delivery. A test certificate can be provided as option.

### 13. QUALITY STANDARDS

All the generating sets meet the following standards: 73/23/CE, 89/392/EE, 89/336/CE, ISO 8528, IEC 34.1. The generators used in our generating sets meet the following standards: ISO 8528, IEC 34.1, CEI 2.3, VDE 0530, BS 4999-5000, NF 51-100.

IVECO and 2HE are fully accredited ISO 9001.

### 14. WARRANTY

Generating set is guaranteed for a period of 12 months from the start up date or 18 months from date of shipment whichever occurs earlier.



www.ivecomotors.com



J.B.Alberdi 7138 - Cap.Fed. - Argentina  
Tel: +54 11 4687-0000