

# Li-Sun Wall Stand Lithium Battery Pack 100Ah-300Ah With 6000/8000+ Cycles

25.6V 100Ah/200Ah/300Ah, 51.2V 100Ah/200Ah/300Ah



## Main Features

- Top brand new LiFePO4 cells, super safety.
- Supports wall mounted or floor stand installation.
- All around protection and unattended operation.
- With Wifi/Bluetooth for easy monitor
- Built inside with fire protection devices
- 5 Years warranty, 6000/8000+ cycles, 10+ years life design.
- 100A/150A/200A Smart BMS matches well with solar system.
- 51.2V battery Integrated with multiple communication protocols for 10+ brands of inverters.
- With battery cable

## Lithium Battery Pack

MODEL	SK-25.6V 100Ah	SK-25.6V 200Ah	SK-25.6V 300Ah	SK-51.2V 100Ah	SK-51.2V 200Ah	SK-51.2V 300Ah
Battery Type	LiFePO4	LiFePO4	LiFePO4	LiFePO4	LiFePO4	LiFePO4
Total Energy	2560Wh	5120Wh	7680Wh	5120Wh	10240Wh	15360Wh
Usable Energy (90%DOD)	2304Wh	4608Wh	6912Wh	4608Wh	9216Wh	13824Wh
Voltage window	22.4~29.2V	22.4~29.2V	22.4~29.2V	44.8~58.4V	44.8~58.4V	44.8~58.4V
Fast Charge Voltage	28.8V	28.8V	28.8V	57.6V	57.6V	57.6V
Folat Charge Voltage	28.0V	28.0V	28.0V	56.0V	56.0V	56.0V
Low DC Cut-off Voltage	23.4V	23.4V	23.4V	46.8V	46.8V	46.8V
Max.continue discharge current	100A	150A	200A	100A	150A	200A
Max.pulse discharge current	150A 1Sec.	200A 1Sec.	300A 1Sec.	150A 1Sec.	150A 1Sec.	300A 1Sec.
Max.continue charge current	50A	100A	150A	50A	100A	150A
Scalable	1~15 in parallel					
Communication	RS485		CAN,RS485			
Cycle life	>8000 Cycles for 300Ah/600Ah >6000 Cycles for 100Ah/200Ah @(+25°C,0.5C,90%DOD,60%EOL)					>8000 Cycles@ (+25°C,0.5C, 90%DOD,60%EOL)
Terminal	double M8					
Storage temperature	0°C~30°C					
Storage duration	6 months at 25°C					
Safety standard	UN38.3,MSDS					
IP degree	IP20					
<b>PROTECTION</b>						
Protection	Over charge protection, Over discharge protection, Over current protection, Shortcircuit protection, Over temperature protection					
<b>AMBIENT</b>						
Working Temperature	-10°C~+50°C					
Humidity	0~95% ( no condensation)					
<b>DIMENSION</b>						
L×W×H (products size)MM	520*390*178	640*390*178	690*455*190	640*390*178	850*560*178	900*625*190
L×W×H (package size)MM	566*440*240 (UN carton)	684*440*240 (UN carton)	739*520*277 (UN wooden cases)	684*440*240 (UN carton)	898*685*265 (UN wooden cases)	948*690*350 (UN wooden cases)
Weight(NW)	32.4	55.0	64.0	55.0	105.2	121.0
Weight(GW)	36.2	60.0	75.0	60.0	121.5	141.0

Smart BMS supports communication with different brand of hybrid inverter

**Casa Fenk S.A.C.I.F.I. • [www.fenk.com.ar](http://www.fenk.com.ar)**

**Avda. J. B. Alberdi 7138 - CABA - Tel.: (5411) - 4687-0000 - [ventas@fenk.com.ar](mailto:ventas@fenk.com.ar)**